

Power supplier – Inverters and Battery start units

Powering the world of aviation

25 years of experience



www.RAMPpower.com

Kruisboommolenstraat 7/9
8800 Roeselare



OUR ADVANTAGES

We stand for top quality products, client first service and worldwide on-time deliveries.

Every delivery comes with all certificates and export documents. Deliveries throughout Europe and the rest of the world are prompt and right on time.

Large stock of components and product line.

Competitive pricing.



OUR FACTORY – ABOUT US

All our products are produced in our factory in Belgium.

We are combining world-leading technologies, advanced power solutions and pioneering digital insights components.

we have modern CNC manufacturing equipment to meet any of your power supply casings. TIG, MIG, MAG, STUD, SPOT, Shearing, laser cutting, rolling, bending, Vertical mill, manual lathe, Hot-dip galvanizing.



Continuous power supply 25 A

Technical data

- 220 V / 110 V single phase input power
- Available with output power of 28VDC/12VDC or 24VDC.
- 25 Amps output power
- Standard with matching aircraft connector AN2551.
- Long quality output cable.
- Low ripple.
- Polarity protection.
- Short cut protection.
- Auto cooling fan.
- Over voltage protection.
- Auto reset circuit breaker.
- Size 300x70x50cm , 9 Kg. We ship all over the world.
- for more information or tailored solutions call us or send us an email
- Air transportable, 'Non Hazardous'
- Maintenance free.
- Tough and compact.
- Portable power at remote locations.

Partnumbers for options

- P/N AP12DC : 25 Amps – 12 VDC with piper connector. (www.aircraftplugs.com)
- P/N AP24DC : 25 Amps – 24 VDC with AN2551 connector.
- P/N AP28DC : 25 Amps – 28VDC with AN2551 connector.



Continuous power supply 100 A – 200 A + COMBI

Technical data

- 220 V / 110 V single phase input power
- Available with output power of 28VDC/12VDC or 24VDC.
- 100 / 200 Amps output power
- Standard with matching aircraft connector AN2551 or rubber connector.
- Long quality output cable.
- Low rimpel.
- Polarity protection.
- Short cut protection.
- Auto cooling fan.
- Over voltage protection.
- Auto reset circuit breaker.
- Size 300x70x50cm , 9 Kg. We ship all over the world.
- for more information or tailored solutions call us or send us an email
- Air transportable, 'Non Hazardous'
- Maintenance free.
- Tough and compact.
- Portable power at remote locations.

Partnumbers for options

- P/N AP12DC : 100 Amps – 12 VDC with piper connector. (www.aircraftplugs.com)
- P/N AP24DC : 100 Amps – 24 VDC with AN2551 connector.
- P/N AP28DC : 100 Amps – 28VDC with AN2551 connector.

For 200A or more specify upon ordering.



Continuous power supply 50 A - 100 A – 200 A + COMBI

Technical data

- 220 V / 110 V single phase input power
- Available with output power of 28VDC/12VDC or 24VDC.
- 100 / 200 Amps output power
- Standard with matching aircraft connector AN2551 or rubber connector.
- Long quality output cable.
- Low rimpel.
- Polarity protection.
- Short cut protection.
- Auto cooling fan.
- Over voltage protection.
- Auto reset circuit breaker.
- Size 300x70x50cm , 9 Kg. We ship all over the world.
- for more information or tailored solutions call us or send us an email
- Air transportable, 'Non Hazardous'
- Maintenance free.
- Tough and compact.
- Portable power at remote locations.

Partnumbers for options

- P/N AP12DC : 100 Amps – 12 VDC with piper connector. (www.aircraftplugs.com)
- P/N AP24DC : 100 Amps – 24 VDC with AN2551 connector.
- P/N AP28DC : 100 Amps – 28VDC with AN2551 connector.

For 200A or more specify upon ordering.



Continuous power supply 50A - 100 A – 200 A

Technical data

- 220 V / 110 V single phase input power
- Available with output power of 28VDC/12VDC or 24VDC.
- 100 / 200 Amps output power
- Standard with matching aircraft connector AN2551 or rubber connector.
- Long quality output cable.
- Digital reading of amps and voltage.
- Polarity protection.
- Short cut protection.
- Auto cooling fan.
- Over voltage protection.
- Auto reset circuit breaker.
- Size 300x70x50cm , 9 Kg. We ship all over the world.
- for more information or tailored solutions call us or send us an email
- Air transportable, 'Non Hazardous'
- Maintenance free.
- Tough and compact.
- Portable power at remote locations.

Partnumbers for options

- P/N AP12DC : 100 Amps – 12 VDC with piper connector. (www.aircraftplugs.com)
- P/N AP24DC : 100 Amps – 24 VDC with AN2551 connector.
- P/N AP28DC : 100 Amps – 28VDC with AN2551 connector.

For 200A or more specify upon ordering.



Continuous power supply 50A - 100 A – 200 A

Technical data

- 220 V / 110 V single phase input power
- Available with output power of 28VDC/12VDC or 24VDC.
- 100 / 200 Amps output power
- Standard with matching aircraft connector AN2551 or rubber connector.
- Long quality output cable.
- Digital reading of amps and voltage.
- Polarity protection.
- Short cut protection.
- Auto cooling fan.
- Over voltage protection.
- Auto reset circuit breaker.
- Size 300x70x50cm , 9 Kg. We ship all over the world.
- for more information or tailored solutions call us or send us an email
- Air transportable, 'Non Hazardous'
- Maintenance free.
- Tough and compact.
- Portable power at remote locations.

Partnumbers for options

- P/N AP12DC : 100 Amps – 12 VDC with piper connector. (www.aircraftplugs.com)
- P/N AP24DC : 100 Amps – 24 VDC with AN2551 connector.
- P/N AP28DC : 100 Amps – 28VDC with AN2551 connector.

For 200A or more specify upon ordering.



Continuous power supply 200 A - 600 A – 1200 A

Technical data

- 220 V / 110 V single phase or 3 phase connector.
- Available with output power of 28VDC/12VDC or 24VDC.
- DC Amps output power
- Standard with matching aircraft connector AN2551 or rubber connector.
- Long quality output cable.
- Low rimpel.
- Polarity protection.
- Short cut protection.
- Auto cooling fan.
- Over voltage protection.
- Auto reset circuit breaker.
- Size 300x70x50cm , 9 Kg. We ship all over the world.
- for more information or tailored solutions call us or send us an email
- Air transportable, 'Non Hazardous'
- Maintenance free.
- Tough and compact.
- Portable power at remote locations.

Partnumbers for options

- P/N AP12DC : 100 Amps – 12 VDC with piper connector. (www.aircraftplugs.com)
- P/N AP24DC : 100 Amps – 24 VDC with AN2551 connector.
- P/N AP28DC : 100 Amps – 28VDC with AN2551 connector.

For 200A or more specify upon ordering.



Continous power supply combi battery start

Technical data

- 220 V / 110 V single phase or 3 phase connector.
- Available with output power of 28VDC/12VDC or 24VDC.
- DC Amps output power + 3200 A or more start power
- Standard with matching aircraft connector AN2551 or rubber connector.
- Long quality output cable.
- Low rimpel.
- Polarity protection.
- Short cut protection.
- Auto cooling fan.
- Over voltage protection.
- Auto reset circuit breaker.
- Size 300x70x50cm , 9 Kg. We ship all over the world.
- for more information or tailored solutions call us or send us an email
- Air transportable, 'Non Hazardous'
- Maintenance free.
- Tough and compact.
- Portable power at remote locations.

Partnumbers for options

- P/N AP12DC : 100 Amps – 12 VDC with piper connector. (www.aircraftplugs.com)
- P/N AP24DC : 100 Amps – 24 VDC with AN2551 connector.
- P/N AP28DC : 100 Amps – 28VDC with AN2551 connector.

For 200A or more specify upon ordering.



Continuous power supply combi battery start

Technical data

- 220 V / 110 V single phase or 3 phase connector.
- Available with output power of 28VDC/12VDC or 24VDC.
- DC Amps output power + 3200 A or more start power
- Standard with matching aircraft connector AN2551 or rubber connector.
- Long quality output cable.
- Low rimpel.
- Polarity protection.
- Short cut protection.
- Auto cooling fan.
- Over voltage protection.
- Auto reset circuit breaker.
- Size 300x70x50cm , 9 Kg. We ship all over the world.
- for more information or tailored solutions call us or send us an email
- Air transportable, 'Non Hazardous'
- Maintenance free.
- Tough and compact.
- Portable power at remote locations.

Partnumbers for options

- P/N AP12DC : 100 Amps – 12 VDC with piper connector. (www.aircraftplugs.com)
- P/N AP24DC : 100 Amps – 24 VDC with AN2551 connector.
- P/N AP28DC : 100 Amps – 28VDC with AN2551 connector.

For 200A or more specify upon ordering.



Continuous power supply combi battery start

Technical data

- 220 V / 110 V single phase or 3 phase connector.
- Available with output power of 28VDC/12VDC or 24VDC.
- DC Amps output power + 3200 A or more start power
- Standard with matching aircraft connector AN2551 or rubber connector.
- Long quality output cable.
- Low rimpel.
- Polarity protection.
- Short cut protection.
- Auto cooling fan.
- Over voltage protection.
- Auto reset circuit breaker.
- Size 300x70x50cm , 9 Kg. We ship all over the world.
- for more information or tailored solutions call us or send us an email
- Air transportable, 'Non Hazardous'
- Maintenance free.
- Tough and compact.
- Portable power at remote locations.

Partnumbers for options

- P/N AP12DC : 100 Amps – 12 VDC with piper connector. (www.aircraftplugs.com)
- P/N AP24DC : 100 Amps – 24 VDC with AN2551 connector.
- P/N AP28DC : 100 Amps – 28VDC with AN2551 connector.

For 200A or more specify upon ordering.



Continous power supply & battery start

Technical data

- 220 V / 110 V single phase or 3 phase connector.
- Available with output power of 28VDC/12VDC or 24VDC.
- DC Amps output power + 3200 A or more start power
- Standard with matching aircraft connector AN2551 or rubber connector.
- Long quality output cable.
- Low rimpel.
- Polarity protection.
- Short cut protection.
- Auto cooling fan.
- Over voltage protection.
- Auto reset circuit breaker.
- Size 300x70x50cm , 9 Kg. We ship all over the world.
- for more information or tailored solutions call us or send us an email
- Air transportable, 'Non Hazardous'
- Maintenance free.
- Tough and compact.
- Portable power at remote locations.

Partnumbers for options

- P/N AP12DC : 100 Amps – 12 VDC with piper connector. (www.aircraftplugs.com)
- P/N AP24DC : 100 Amps – 24 VDC with AN2551 connector.
- P/N AP28DC : 100 Amps – 28VDC with AN2551 connector.

For 200A or more specify upon ordering.

Technical data

- Available with output power of 28VDC/12VDC or 24VDC.
- 28.5V DC auto stabilization (no adjustments ever required by operators)
- Over Voltage aircraft protection - with fault indicator light
- Under Voltage protection provided by Hybrid-Battery pack at 24V DC or 28VDC
- Simple contactor on/off switch with indicator
- Aircraft Engine Hot Start Protection: 28V starting power remains in hybrid batteries in event of engine fault
- Low profile provides excellent view of aircraft and cable connection to the aircraft
- All rounded edges greatly limit the potential for aircraft and unit damage
- Stainless steel construction.
- Tailor made constructions with 400 Hz setups are welcome.





LOADBANK P/N APLB100

Technical data

- 2500A max – 5 min
- Continue 350 A
- Aluminium construction
- 6 Heavy duty cooling fans in aluminium.
- Engine starts simulation, 2500A.
- Light weight.
- Tailor made loadbank request are welcome.
- Test sockets available.
- Wireless readout optional.
- Digital readout of all parameters.

Partnumbers for options

- P/N APLB100DC : 2500Amps – loadbank
- P/N APLB500 DC : 1000 loadbank
- P/N APLB50 : Continue 200 Amps loadbank - No start simulation



- 15 KVA – 400 HZ .
- Aluminium Cassing
- Heavy duty support wheels.
- Digital readout.
- ISO461 connector.
- Heavy duty cooling fans





We do offer repair on outlet cables and GPU connectors of any brand of GPU.

Power supply unit repair & refurbishment. Power supply repairs for all types of electronics: linear and switched power supplies, DC/DC converters, inverters.



CONTACT

RAMP power
Industrialzone Strohof
Kruisboommolenstraat 7/9
8800 Roeselare
Belgium

www.ramppower.com
info@ramppower.com

+32.51.77.99.19